

B809

DISCREET HIGH- PERFORMANCE

PRESCRIPTION
FRAME

★ EXCELLENCE



B809BL



B809BXL



31 g - size L
33 g - size XL



SUPPLIED WITH

Hard case,
microfibre cloth



FRAME

• TR90/Metal/Nylon

LENS MATERIAL AVAILABLE

• CR39
• Polycarbonate

- + BUILT-IN SIDE SHIELDS
- + ADJUSTABLE REINFORCED TEMPLES
- + NOSE BRIDGE WITH NON-SLIP PADS
- + RIVETED SIDE SHIELDS
- + LARGE SIZES: L AND XL

bolle
SAFETY

B809

DISCREET HIGH- PERFORMANCE

MODEL		REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
B809	Black temples – Large	B809BL	54/17	EN166 F CE	127 mm
	Black temples - Extra large	B809BXL	57/17	EN166 F CE	130 mm

LENS MARKING

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.


CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

CE European standard  Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +10/-10

Maximum cylinder compared with sphere : +/-6.

CORRECTED BASE:

Corrected base : 4

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE		
	B809BL	B809BXL
Per piece	3660740009106	3660740008376

CHARACTERISTICS	
LENS MATERIALS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Degressive
FRAME MATERIALS	TR90/Metal/Nylon



18/03/2019

Europe Bollé Safety
34 rue de la Soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : uk@bollebrands.com

bolle
SAFETY